





LUNGA GITTATA / LONG RANGE



13.901.151



Standard con ugello LUNGA GITTATA Ø4.5 - attacco G1/2M.

Foro max. ugello: Ø7.0
Pressione di esercizio max.: 60 bar
Peso: 1.6 kg
Lunghezza: 700 mm

Materiali: ottone - acciaio inox - materiali plastici ad alta resistenza.

Impiego: trattamenti antiparassitari di colture ad alto fusto ed interventi di protezione civile. Portate e gittate elevate (fino a 110 l/min e 22 m). Nuovo design per corpo, impugnature e protezione con riduzione del peso. Angolo di spruzzo regolabile con l'impugnatura anteriore che può contenere un ugello di ricambio. Robusta e versatile. Ugello protetto dagli urti.

Standard with LONG RANGE spray tip Ø4.5 - 1/2" BSPM. connection

Max. spray tip hole: Ø7.0
Max operating pressure: 60 bar / 850 psi
Weight: 1.6 kg / 3.5 lb
Length: 700 mm / 27.5"

Materials: brass - stainless steel - high resistance plastic materials

Use: high pressure spraying on tall trees, forest fire control. Higher capacity and throw performances (up to 110 l/min - 29 USGal/min and 22 m - 70 ft). Improved weight saving design for body, handles and protection. Front handle, for easy spray adjustment, can hold a spare spray tip. Sturdy and versatile. Spray tip shock proof protection.

COME SI ORDINA / HOW TO ORDER

CODICE
code

13.901.151



5

KIT
RICAMBIO
spare parts kit

7.302.1



PAGE 25



PAGE 20

