



Condizioni di esercizio

Work conditions

DN	3/8"
P (bar)	50
P (PSI)	720
T (°C)	-15 +80

POS.	CODICE / CODE	DENOMINAZIONE	DENOMINATION	MATERIALE	MATERIAL
1	TOIR 1050 010 020	DADO 3/8"	NUT 3/8"	OTTONE UNI EN 12164	UNI EN 12164 BRASS
2	TOIR 1130 010 009	CALOTTA M24x1,5	CAP M24x1,5	OTTONE UNI EN 12164	UNI EN 12164 BRASS
3	TOIR 1130 010 008	RACCORDO SFERICO 3/8"	SPHERIC CONNECTION 3/8"	OTTONE UNI EN 12164	UNI EN 12164 BRASS
4	FOIR 1140 010 013	RACCORDO CURVO M24x1,5 x M25x1,5	CURVED CONNECTION M24x1,5 x M25x1,5	OTTONE UNI EN 1982	UNI EN 1982 BRASS
5	SOIR 1140 010 001	CORPO	BODY	OTTONE UNI EN12165	UNI EN 12165 BRASS
6	DAAC 0092 150 006	DADO AUTOBLOCCANTE M12	SELF LOCKING NUT M12	ACCIAIO ZINCATO	ZINC PLATED STEEL
7	ROAC 1140 010 014	RONDELLA Ø25x12x2,5	WASHER Ø25x12x2,5	ACCIAIO ZINCATO	ZINC PLATED STEEL
8	TAIR 1140 010 018	TUBO Ø24 x 1 x L60	PIPE Ø24 x 1 x L60	ACCIAIO INOX AISI 304	AISI 304 STAINLESS STEEL
9	TOIR 1140 010 015	TUBO Ø8 x 1 x L74	PIPE Ø8 x 1 x L74	OTTONE UNI EN 12168	UNI EN 12168 BRASS
10	TOIR 1170 015 026	RONDELLA Ø23 x 18 x 2	WASHER Ø23 x 18 x 2	OTTONE UNI EN 12168	UNI EN 12168 BRASS
11	TOIR 1140 330 010	CONVOGLIATORE Ø20	CONVEYOR Ø20	OTTONE UNI EN 12164	UNI EN 12164 BRASS
12	SOIR 1170 015 020	TESTA M25x1,5	HEAD M25x1,5	OTTONE UNI EN 12165	UNI EN 12165 BRASS
13	..OR 1130 010 007	OR 115 (Øi 11,91x2,62)	O RING 115 (Øi 11,91x2,62)	GOMMA NBR 75	NBR 75 RUBBER
14	TOIR 1130 010 005	TESTINA	SMALL HEAD	OTTONE UNI EN 12164	UNI EN 12164 BRASS
15	UGEL B71C 015 000	BUSSOLINA B71C foro 1,5	B71C INSET 1,5 hole	CERAMICA	BAKED CLAY
16	SPIR 1170 015 019	PARASPRUZZO	SPRINKLING-GUARD	NYLON + VETRO	NYLON + GLASS
17	SEEG 1170 015 028	ANELLO DI ARRESTO UNI 7433	STOP RING UNI 7433	ACCIAIO ZINCATO	ZINC PLATED STEEL
18	..OR 1027 015 002	OR 117 (Øi 13,10x2,62)	O RING 117 (Øi 13,10x2,62)	GOMMA NBR 75	NBR 75 RUBBER
19	TOIR 1140 010 003	MASCHIO	SHUTTING CONE	OTTONE UNI EN 12164	UNI EN 12164 BRASS
20	..OR 1070 006 004	OR 121 (Øi 15,88x2,62)	O RING 121 (Øi 15,88x2,62)	GOMMA NBR 75	NBR 75 RUBBER
21	SAIR 1140 010 016	LEVA GRADUATA CORTA	SHORT GRADUATED LEVER	ACCIAIO ZINCATO	ZINC PLATED STEEL
22	UGEL U71C 015 000	UGELLO U71C foro 1,5	U71C NOZZLE 1,5 hole		